Enclosed Rotary Screw Compressors

5, 7.5, 10, 15, and 20 horsepower compressors

Features & Benefits

- Air end manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL control components
- Automatic belt tensioning
- Omega profile rotors
- Air/oil cooler
- · Easy to access oil cooler for cleaning

- Operating pressures from 100-190 PSI
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- · Factory filled with premium synthetic fluid
- Solid steel sound enclosure
- Vertical draft ventilation
- ASME Powder coated air receiver
- Heavy duty air filter
- TEFC drive motor (3 phase only)
- Free freight included on elite models



Order Guide

Part Number	ACFM @ 150 PSI	Phase	HP	Voltage	Tank Size
RTRS71ENC3-1B	26	1	7.5	208-230	80 gallon, horizontal
RTRS73ENC3-2B	26	3	7.5	208-230v	80 gallon, horizontal
RTRS103ENC3-2B	39	3	10	208-230v	80 gallon, horizontal
RTRS103ENC3-4B	39	3	10	480v	80 gallon, horizontal
RTRS153ENC3-2B	54	3	15	208-230v	80 gallon, horizontal

For Elite versions, add 'E' instead of 'B'. | For more sizes and options, call factory.



CA PROPOSITION 65 WARNING WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov/product

@rti_pbe

(0)