Open Rotary Screw Compressors

5, 7.5, and 10 horsepower compressors

Features & Benefits

- Air end manufactured with German rotary screw components
- Spin on separator
- · Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL control components
- · Omega profile rotors
- Air/oil cooler
- · Easy to remove bolt on oil cooler for cleaning

- Operating pressures from 100-190 PSI
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- · Factory filled with premium synthetic fluid
- ASME Powder coated air receiver
- Heavy duty air filter
- TEFC drive motor (3 phase only)
- Free freight included on elite models



Order Guide

Part Number	Phase	НР	Voltage	Tank size	Length (in.)	Width (in.)	Height (in.)
RTRS51V80-1B	1	5	208-230	80 gallon, vertical	32.0	24.0	76.0
RTRS53V80-2B	3	5	208-230v	80 gallon, vertical	32.0	24.0	76.0
RTRS51H80-1B	1	5	208-230	80 gallon, horizontal	60.0	24.0	45.0
RTRS53H80-2B	3	5	208-230v	80 gallon, horizontal	60.0	24.0	45.0
RTRS71V80-1B	1	7.5	208-230	80 gallon, vertical	32.0	24.0	76.0
RTRS73V80-2B	3	7.5	208-230v	80 gallon, vertical	32.0	24.0	76.0
RTRS71H80-1B	1	7.5	208-230	80 gallon, horizontal	60.0	42.0	45.0
RTRS73H80-2B	3	7.5	208-230v	80 gallon, horizontal	60.0	24.0	45.0
RTRS103V80-2B	3	10	208-230v	80 gallon, vertical	32.0	24.0	76.0
RTRS103H80-2B	3	10	208-230v	80 gallon, horizontal	60.0	24.0	45.0

For Elite versions, add 'E' instead of 'B'. | For more sizes and options, call factory.

CA PROPOSITION 65 WARNING















