Open Rotary Screw Compressors

Ai006_1217

5, 7.5, and 10 horsepower compressors

Features & Benefits

- Air end manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL control components
- Omega profile rotors
- Air/oil cooler
- Easy to remove bolt on oil cooler for cleaning
- Operating pressures from 100-190 PSI
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- Factory filled with premium synthetic fluid
- ASME Powder coated air receiver
- Heavy duty air filter
- TEFC drive motor (3 phase only)
- Free freight included on elite models

Order Guide

Part Number	Phase	HP	Voltage	Tank size	Length (in.)	Width (in.)	Height (in.)
RSV-815-19-B	1	5	208-230	80 gallon, vertical	32.0	24.0	76.0
RSV-835-19-B	3	5	208-230-460	80 gallon, vertical	32.0	24.0	76.0
RSH-815-19-B	1	5	208-230	80 gallon, horizontal	60.0	24.0	45.0
RSH-835-19-B	3	5	208-230-460	80 gallon, horizontal	60.0	24.0	45.0
RSV-817.5-29-B	1	7.5	208-230	80 gallon, vertical	32.0	24.0	76.0
RSV-837.5-29-B	3	7.5	208-230-460	80 gallon, vertical	32.0	24.0	76.0
RSH-817.5-29-B	1	7.5	208-230	80 gallon, horizontal	60.0	42.0	45.0
RSH-837.5-29-B	3	7.5	208-230-460	80 gallon, horizontal	60.0	24.0	45.0
RSV-8110-42-B	1	10	208-230	80 gallon, vertical	32.0	24.0	76.0
RSV-8310-42-B	3	10	208-230-460	80 gallon, vertical	32.0	24.0	76.0
RSH8110-42-B	1	10	208-230	80 gallon, horizontal	60.0	24.0	45.0
RSH-8310-42-B	3	10	208-230-460	80 gallon, horizontal	60.0	24.0	45.0

For Elite versions, add 'E' instead of 'B'. | For more sizes and options, call factory.