

Eliminizer® Combo units for Industrial Applications



3P-060-M04-DC

Model #	Height (in.)	Width (in.)	Depth (in.)	Weight (lbs.)
3P-020-M02-DC	6.8	6.5	3.0	4.0
3P-060-M03-DC	10.5	8.0	3.8	9.0
3P-060-M04-DC	10.5	8.0	3.8	9.0
3P-090-M04-DC	17.5	10.0	4.6	16.0
3P-090-M06-DC	17.5	10.0	4.6	16.0
3P-150-M08-DC	17.5	10.0	4.6	16.0

Model #	Rated Flow (SCFM)	Port Size (in.)	Drain	Bowl O-Ring	DPI	1st Stage Element	2nd Stage Element
3P-020-M02-DC	20	¼	N32-95-979	N32-95-257	optional	3P-060	3C-060
3P-060-M04-DC	60	½	N32-95-979	N32-95-257	optional	3P-060	3C-060
3P-090-M04-DC	90	½	N32-95-979	N32-95-256	optional	3P-090	3C-090
3P-090-M06-DC	90	¾	N32-95-979	N32-95-256	optional	3P-090	3C-090
3P-150-M08-DC	150	1	N32-95-979	N32-95-256	optional	3P-150	3C-150

Standard maximum air pressure is 150 PSIG for polycarbonate bowls. The metal bowl will accommodate 200 PSIG. For applications requiring pressure vessels up to 500 PSIG, consult the factory. Rated flow is measured at inlet air pressure of 100 PSIG.

Notes

1. For high pressure applications from 150 to 500 psig, consult the factory.
2. For applications where hostile chemicals are present in the environment, install only metal bowl assemblies without indicators.
3. Units manufactured with the indicators add 1" to overall height of the unit
4. Units with indicators add "i" to the part numbers

Applications

Eliminizer® Combos will remove water, dirt and oil as small as 0.01 micron with 99.99998% efficiency. To extend the life of the combo units, install Eliminex® Combo units in the mainline.

Installation

Install units in a vertical position with the drains pointing downward and the air flowing in the direction indicated by the arrow on the castings. Install unit as close as possible to the point of use. Always place unit before regulator.

Service

Do not attempt to service the unit with the air pressure in the bowls; always bleed the air from the unit prior to disassembly. Replace element in the 1st stage every 6-9 months, and the 2nd stage every 12 months. Service the drain on a regular 3 month interval to ensure proper function and performance of the unit. This entails area cleaning/debris removed and soapy water bath of the drain.



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe

